



MODEL GF-500 OVERHEAD EMERGENCY SHOWER

Features:

- | | |
|---|---|
| <ul style="list-style-type: none"> • Polyethylene Tank & Shower Assembly • Meets ANSI Standard Z358.1-1998 • 2" Quick Connect Fill Line • 18" Inspection Port | <ul style="list-style-type: none"> • All Structural Steel Hot Dip Galvanized • Factory Testing of Flow Rates and System Integrity • One Day Free Training at Our Facility • Operation and Instruction Manual |
|---|---|



Orbit Industries' Model GF-500 is a free standing gravity fed portable emergency shower designed for use at remote locations that do not have standard water or electrical service. The Model GF-500 utilizes a 500 gallon overhead reservoir and the natural force of gravity to deliver water to the shower head and eyewash. All showers meet ANSI standards (Z358.1-1998). Each shower / eye wash system is factory tested for flow rate and spray pattern before shipment. Complete material documentation, including seismic calculations material test reports for all structural steel, factory test data, and OEM part brochures can be included at your request. Orbit Industries can train your personnel at our site, in the safe operation and maintenance of this equipment.

Orbit's design team can add options to meet any requirement. Heated shower option features an insulated tank, heat-tracing to prevent freezing, and a water heating system. Controls feature a simple on/off power switch with GFCI breaker, requiring 120 VAC, 30 Amp, Single Phase power. Other options include, portable gas or diesel drive electrical generator, 240 Volt electrical (required for heated units), trailer mounted, skid mounted, fully enclosed, explosion proof electrical panel and components.

SHOWER SPECIFICATIONS:

- **SHOWER FLOW RATE** ... 20 GPM FOR 15 MINUTES MINIMUM
- **EYEWASH FLOW RATE**... 3 GPM FOR 15 MINUTES MINIMUM
- **WATER TANK CAPACITY**.....500 Gallon

